

WHAT IS CLAIMED IS:

- 16

2. The invention defined in Claim 1 wherein at least one of said jaws is provided with apertures extending therethrough.

3. The invention defined in Claim 1 wherein said spring means includes an elongate elastomeric member.

4. The invention defined in Claim 1 wherein said spring means is attached to at least one of the walls and to the pinion.

5. The invention defined in Claim 4 wherein said spring means includes an elongate elastomeric member.

6. The invention defined in Claim 5 wherein said spring means is attached to at least one of the walls and the pinion.

7. The invention defined in Claim 6 wherein the pinion includes a laterally extending support for the spring means.

8. The invention defined in Claim 1 wherein at least one of the side walls is provided with slots for vertical guiding the rack.

0972519-013004

15. The invention defined in Claim 1 wherein said bucket includes side walls with corners, thereby allowing thinner wall sections and retaining strength.

16. The invention defined in Claim 1 wherein a seal is formed by said bucket and said wringer, said seal preventing liquid from exiting therebetween.

17. The invention defined in Claim 1 wherein said wringer sits on three sides of said bucket.

09773649 013004

18. A mop bucket and wringer apparatus for wringing liquid from a mop comprising:

a mop bucket having an open interior terminating in an upwardly facing opening defined by a marginal rim; and

a mop wringer including means for selective attachment to the marginal rim of said bucket; said wringer including:

an upwardly opening for receiving a mop and defined by front, rear, side, and bottom walls at least some of which are provided with passageways to allow liquids to pass therethrough;

at least one pressure plate;

a linkage means mounting the pressure plate in a substantially vertical disposition whereby horizontal movement of the linkage means causes relative movement of the pressure plate toward the front wall of said wringer; and

a spring means normally urging the pressure plate in a substantially vertical position.